



Image Shown may not Reflect Actual Package

UL 10 AMP BATTERY CHARGER

This battery charger offers accurate, automatic charging of lead-acid and nickel cadmium batteries. The output voltage automatically adjusts to changing input, load, battery and ambient conditions. This prevents battery over-charging and consequent loss of battery electrolyte.

Standard features include AC line compensation, precision voltage regulation, current limiting, automatic 2-rate charging, voltmeter and ammeter, temperature compensation and UL Listing.

The user interface is easy to understand with digital metering, NFPA 110 alarms and a battery fault alarm.

SPECIFICATION

Input Supply	110-120 V 208-240 V
AC and DC Fuses	(2 input and 2 output)
Output voltage	24V
Frequency	50/60 Hz
Operating temperature	-20°C (-4°F) to +60°C (140°F)

Housing constructed of rustproof anodized aluminum.

STANDARDS

- C-UL listed to UL 1236
- NFPA 70, NFPA 110
- CSA 22.2 No 107 certified
- UL 1564
- CE DOC to EN 60335
- IBC Seismic Certification

FEATURES

- Electronically current limited at 105% of rated output
- Alarm system
- Digital Display
- Lightning and voltage transient protection
- Protection of connected equipment against load dump protection
- Constant voltage, current limited, 4-rate automatic equalization
- IP 20 housing
- AC isolated from DC
- Temperature Compensation
 - On board temperature sensor with remote port
- Auto AC line compensation
- Output regulated by sensed battery voltage

